

Humidity Meter



Model: HT-6290

Applications

Be able to measure Humidity, Temperature. Widely used in workshops, offices, libraries, computer stations, laboratories and warehouses.



Features

- * The Last Values / Max. Values / Min. Values of both Humidity and Temperature will be automatically stored in memory and can be displayed by turn.
- * The use of durable, long-lasting components, including a strong, light weight ABS-plastic housing assures maintenance free performance for many years. The housing has been carefully shaped to fit in either hand.
- * Used the exclusive MICRO-COMPUTER LSI circuit and crystal time base to offer the high accuracy measurement & fast measuring time.
- * Digital display gives exact reading with no guessing.
- * Wide measuring range & high resolution.

Specifications

Model	HT-6290	
Display	LCD	
Range	Humidity	10~95%RH
	Temp.	-10~60°C(14~140°F)
Resolution	Humidity	0.1%RH
	Temp.	0.1°C / 0.1°F
Accuracy	Humidity	2.5% ± 1%RH
	Temp.	± 0.5°C
Sensor	Humidity	Capacitor
Type	Temp.	Resistor

Sampling Time	0.4 Seconds
Memory	Last Value, Max. Value, Min Value
Time Base	Quartz Crystal
Power Supply	4x1.5V AA (UM-3) Battery
Power Consumption	About 20 mA
Dimensions	161 x 69 x 32 mm (6.6 x 2.7 x 1.3 inch)
Weight	300 g / 0.65 lb (Including Batteries)
Standard Accessories	Main Unit
	Carrying Case (B01)
	Operation Manual